Samsung 55" Crystal UHD 4K Signage QE55T

Brand : Samsung Product family: QET Product code: LH55QETELGCXEN

Product name : 55" Crystal UHD 4K Signage QE55T

- Upscale your business
- Incredible UHD picture quality
- Crisp and vivid color expression

55", LED, 4K UHD (3840 x 2160), 300 nit, 4000:1, 89/89, 6.5 ms, RJ-45, HDCP, HDMI, RS232, AC 100-240V, 50/60Hz, 1230.5 x 707.2 x 59.9 mm, 14.1 kg

Samsung 55" Crystal UHD 4K Signage QE55T. Product design: Digital signage flat panel. Display diagonal: 139.7 cm (55"), Display resolution: 3840×2160 pixels, Display brightness: 300 cd/m^2 , HD type: 4K Ultra HD. Operating system installed: Tizen 4.0. Product colour: Black





Display		Design	
LED backlight	120.7 (FFII)	Panel mounting interface Bezel colour	200 x 200 mm Black
Display diagonal * Display resolution *	139.7 cm (55") 3840 x 2160 pixels	Performance	DIGCK
Display brightness * HD type * Touchscreen *	300 cd/m² 4K Ultra HD	Purpose * HDCP HDCP version	Commercial 2.2
Response time	6.5 ms	Power	2.2
Contrast ratio (typical) Dynamic contrast ratio marketing name	4000:1 Mega DCR 89°	Power consumption (typical) * Power consumption (sleep)	154 W 0.5 W
Viewing angle, vertical Pixel pitch Display diagonal (metric) Horizontal scan range 89° 0.105 x 0.315 mm 138 cm 15 - 135 kHz	89°	Energy efficiency class (SDR) Energy consumption (SDR) per 1000 hours	105 KWN
		AC input voltage AC input frequency Energy efficiency scale	100 - 240 V 50/60 Hz A to G
Haze rate	2%	Computer system	
Pixel frequency (max) Colour gamut	594 MHz 72%	Operating system installed	Tizen 4.0
	1270	Weight & dimensions	
Ports & interfaces HDMI ports quantity * HDMI version HDMI input ports quantity	2 2.0 2	Display width Display depth Display height Display weight	1230.5 mm 59.9 mm 707.2 mm 14.1 kg
DVI port *	X	Packaging data	
USB port * USB ports quantity 1 Ethernet LAN * Wi-Fi * ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓	1	Package width Package depth Package height Package weight	1386 mm 158 mm 843 mm 20.2 kg
Audio (L/R) out	1	Operational conditions	
RS-232 interface Design	✓	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 80%
•	Digital signage flat panel	Certificates	10 00/0
Placement supported * Product colour *	Indoor Black	Certification	Class B 60950-1

Design		Other features	
Screen shape	Flat	Flash memory	8000 MB
VESA mounting *	✓	Optional features	WMN4070SE STN-L4355F



8806090505195

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.